

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 913 468 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
13.06.2001 Bulletin 2001/24

(51) Int Cl.7: **A21D 8/04**, C12N 9/98,
C12N 11/04

(43) Date of publication A2:
06.05.1999 Bulletin 1999/18

(21) Application number: **98202389.7**

(22) Date of filing: **16.07.1998**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Piljter, Johannes Jozef**
2291 JV Wateringen (NL)
• **Meesters, Gabriel Marinus Henricus**
2614 TJ Delft (NL)

(30) Priority: **22.07.1997 EP 97202292**

(74) Representative:
Matulewicz, Emil Rudolf Antonius, Dr. et al
DSM Patents & Trademarks
Office Delft
P.O. Box 1
2600 MA Delft (NL)

(71) Applicant: **DSM N.V.**
6411 TE Heerlen (NL)

(54) **Bread improving composition**

(57) This invention relates to a coated lipase granule

comprising lipase coated with a material which is imper-
vious to lipid.

EP 0 913 468 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 2389

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 97 12958 A (GENENCOR INT) 10 April 1997 (1997-04-10) * page 1, paragraph 1 - last line; claims 1,2 * * page 2, paragraph 4 - page 4, paragraph 4 * * page 5, paragraph 1 * ---	1-4,6-13	A21D8/04 C12N9/98 C12N11/04
X	US 4 740 469 A (NISHINAKA MASAYUKI ET AL) 26 April 1988 (1988-04-26)	1-7	
Y	* column 1, line 12 - line 16; claims 1,2,5,8-10,13,16 * * column 2, line 12 - column 3, line 20 * ---	8-13	
D,Y	WO 94 04035 A (NOVONORDISK AS ;OLESEN TINE (DK); QI SI JOAN (DK); DONELIAN VAHAN) 3 March 1994 (1994-03-03) * page 1, line 5 - line 10; claims 1,13,14 * * page 10, line 17 - line 28 * ---	8-13	
X	EP 0 304 332 A (NOVO INDUSTRI AS) 22 February 1989 (1989-02-22) * page 2, line 3 - line 7 * * page 2, line 28 - line 34 * * page 2, line 50 - page 3, line 4 * ---	1-7	TECHNICAL FIELDS SEARCHED (Int.Cl.6) A21D C12N
X	WO 94 26883 A (GIST BROCADES NV ;ANDELA CARL SIDONIUS MARIA (NL); FEIJEN JAN (NL)) 24 November 1994 (1994-11-24) * page 1, line 6 - line 7 * * page 3, line 14 - line 19 * * page 5, line 9 - line 20 * * page 5, line 26 - line 34 * ---	1-5	
		-/--	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 April 2001	Examiner Charles, D
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document	

EPO-CHM 1503 03 82 (P04001)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 2389

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 93 07260 A (GENENCOR INT) 15 April 1993 (1993-04-15) * page 1, paragraph 1; claims 1,3,4,9 * * page 6, paragraph 1 - page 7, paragraph 1 * * page 9, paragraph 2 * * page 12, paragraph 1 * ---	1-5	
X	US 5 258 132 A (KAMEL AHMED A ET AL) 2 November 1993 (1993-11-02) * column 1, line 13 - line 17; claims 1,7,11 * * column 5, line 1 - line 10 * * column 6, line 27 - line 33 * * column 9, line 53 - column 10, line 3 * ---	1-4	
X	US 4 689 297 A (GOOD IVAN C ET AL) 25 August 1987 (1987-08-25) * column 1, line 6 - line 8; claims 1-6 * * column 2, line 5 - line 29 * * column 3, line 25 - column 4, line 9 * ---	1-4	
D,A	EP 0 585 988 A (GIST BROCADES NV) 9 March 1994 (1994-03-09) * page 2, line 1 - line 7; claims 1,2,5,9 * * page 2, line 29 - line 30 * * page 3, line 3 - line 4 * -----	8-14	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 April 2001	Examiner Charles, D
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04201)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 20 2389

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-04-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9712958 A	10-04-1997	AU 718010 B	06-04-2000
		AU 7392496 A	28-04-1997
		EP 0862623 A	09-09-1998
		US 6120811 A	19-09-2000
US 4740469 A	26-04-1988	JP 1830119 C	15-03-1994
		JP 61092570 A	10-05-1986
		AU 579410 B	24-11-1988
		AU 4850885 A	17-04-1986
		CA 1242663 A	04-10-1988
		GB 2167758 A, B	04-06-1986
WO 9404035 A	03-03-1994	AT 200006 T	15-04-2001
		EP 0659049 A	28-06-1995
		US 6110508 A	29-08-2000
EP 0304332 A	22-02-1989	AT 91500 T	15-07-1993
		DE 3882301 A	19-08-1993
		DE 3882301 T	21-10-1993
		DK 436888 A, B,	22-02-1989
		JP 1112983 A	01-05-1989
		JP 2647695 B	27-08-1997
		MX 12725 A	01-08-1993
WO 9426883 A	24-11-1994	AU 677342 B	17-04-1997
		AU 6970594 A	12-12-1994
		CA 2140530 A	24-11-1994
		CN 1110059 A	11-10-1995
		EP 0675952 A	11-10-1995
		FI 950183 A	16-01-1995
		PL 307854 A	26-06-1995
WO 9307260 A	15-04-1993	CA 2120611 A	15-04-1993
		EP 0620848 A	26-10-1994
		FI 941645 A	08-04-1994
		JP 6511381 T	22-12-1994
US 5258132 A	02-11-1993	US 5230822 A	27-07-1993
		AU 633645 B	04-02-1993
		AU 6597090 A	23-05-1991
		BR 9005786 A	24-09-1991
		CA 2029658 A	16-05-1991
		DE 69031824 D	29-01-1998
		DE 69031824 T	30-04-1998
		EP 0436971 A	17-07-1991
		ES 2110407 T	16-02-1998

EPO FORM P458

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 20 2389


This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-04-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5258132 A		JP 3185099 A	13-08-1991
		US 5200236 A	06-04-1993
		ZA 9009178 A	29-07-1992
		AU 652438 B	25-08-1994
		AU 1510792 A	17-09-1992
		BR 9201531 A	01-12-1992
		CA 2066871 A,C	25-10-1992
		DE 69201589 D	13-04-1995
		DE 69201589 T	13-07-1995
		EP 0510761 A	28-10-1992
		ES 2071418 T	16-06-1995
		JP 6313200 A	08-11-1994
		JP 8026360 B	13-03-1996
		ZA 9202982 A	25-10-1993
US 4689297 A	25-08-1987	BR 8600926 A	11-11-1986
		CA 1267622 A	10-04-1990
		DE 3681468 A	24-10-1991
		DK 98186 A	06-09-1986
		EP 0193829 A	10-09-1986
		ES 552640 D	16-03-1987
		ES 8704203 A	01-06-1987
		JP 1997645 C	08-12-1995
		JP 4006351 B	05-02-1992
		JP 61209589 A	17-09-1986
		JP 2509073 B	19-06-1996
		JP 6062857 A	08-03-1994
		MX 163251 B	24-03-1992
EP 0585988 A	09-03-1994	AT 135163 T	15-03-1996
		AU 4216693 A	03-02-1994
		CA 2101308 A	28-01-1994
		DE 69301796 D	18-04-1996
		DE 69301796 T	01-08-1996
		DK 585988 T	24-06-1996
		ES 2087646 T	16-07-1996
		GR 3019731 T	31-07-1996
		JP 6169681 A	21-06-1994

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 913 468 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
06.05.1999 Bulletin 1999/18

(51) Int. Cl.⁶: **C12N 9/88, A21D 8/04**

(21) Application number: **98202389.7**

(22) Date of filing: **16.07.1998**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **22.07.1997 EP 97202292**

(71) Applicant: **GIST-BROCADES B.V.
2600 MA Delft (NL)**

(72) Inventors:
• **Piljter, Johannes Jozef
2291 JV Wateringen (NL)**
• **Meesters, Gabriel Marinus Henricus
2614 TJ Delft (NL)**

(74) Representative:
**Matulewicz, Emil Rudolf Antonius, Dr. et al
Gist-Brocades BV
Patents and Trademarks Department
Wateringseweg 1
P.O. Box 1
2600 MA Delft (NL)**

(54) **Bread Improving composition**

(57) This invention relates to a coated lipase granule comprising lipase coated with a material which is impervious to lipid.

EP 0 913 468 A2

Description

[0001] The present invention relates to a novel bread improving composition and its uses.

[0002] In recent years enzymes have been used to an increasing extent as highly useful aids to facilitate baking processes and improve the quality of baked products.

[0003] The use of lipase (EC 3.1.1.3) combined with other enzymes in baking is known (see European Patent EP 0585 988 B1 or International application WO 94/04035). Lipase catalyses the hydrolysis of triglycerides (lipids) into mono- and diglycerides and free fatty acids. Whereas the amount of such lipids is relatively low (0.5-2%) in the flour made from most cereal crops. Many compositions used in the baking industry to improve the properties of bread contain substantial amounts of fats. We have found that lipase, when present in such compositions, generates free fatty acids during storage which strongly shortens the shelf-life of the compositions.

[0004] Coating of enzyme granules is used to prevent the formation of enzyme dust, especially for enzymes used in detergents. The enzyme granules may be coated with a material which forms a film. Such a coating is used to prevent dust formation, rather than to form a barrier between the enzyme and for other compounds, such as fats.

[0005] Theoretical calculations show that such a coating would not prevent fat penetrating into the enzyme particle.

[0006] Lipase is an enzyme which is still active at very low water concentrations. Since the compositions added to improve bread properties have a concentration of water higher than the water concentrations at which lipase is active, lipase in these compositions would be active.

[0007] Although the diffusion coefficients of lipids in the coating material of enzyme particles is not known, one can estimate the value of these coefficients based on the coefficients known for other materials.

[0008] For proteins (eg. enzymes) in cheese the diffusion constant is $10^{-12} \text{ m}^2/\text{s}$. So the lowest diffusion coefficient for lipids would be in the order of $10^{-15} \text{ m}^2/\text{s}$ (this is two orders of magnitude lower than diffusion coefficient in bitumen). In reality the diffusion constant of lipids in the coating material is probably higher than this.

[0009] The thickness of the coating on the granule of course varies, but the upper limit is in the range of 25 μm .

[0010] Based on the assumption that the effective diffusion coefficient is $10^{-15} \text{ m}^2/\text{s}$ one can calculate the distance within the coating at which the lipid concentration is halved per unit time. As an example for one second this distance is 32 nm, for one hour 2 μm . Similar calculations for 25 μm of coating material the upper limit of the thickness of the coating layer show that after 7 days the lipid concentration at the lipase is already half of the

concentration of that in the composition. Some granules have a coating which is less than 25 μm . Therefore for these the time needed for the lipid concentration at the lipase to be half that in the composition would be much shorter, since the time and distance are related to each other by a power factor of 2 (so either square or square root depending on the formulation of the equation used).

[0011] From further calculations one can conclude that even after one day lipid has already reached the enzyme inside the coated particle and therefore the lipid break down products which cause rancidity are being formed. However the times which are being estimated in these calculations are the upper limits for how long it will be to the start of lipase activity. In practice one should expect shorter times, as the diffusion coefficient is probably at least one order of magnitude larger. In addition, there is variation in the thickness of the coating, therefore it will often be much less than 25 μm and hydrolysis of the lipid will begin as soon as any lipid has reacted the enzyme.

[0012] Therefore, the use of materials which form films to coat the lipase would not be expected to solve the problem of how to substantially reduce fat hydrolysis.

[0013] Surprisingly, we have found a coat formulation for the lipase which substantially reduces the amount of fat degradation which occurs during the storage period of the composition. In addition, the enzyme becomes fully active as soon as water is added by the baker in the mixer.

[0014] We found that the coat formulation for the lipase prevents the occurrence of rancidity when the lipase granules are added to compositions containing lipids. This is surprising because as discussed above understanding of the physical and biochemical aspects of the system would lead one to expect that rancidity would occur.

[0015] Therefore, the lipase granule is coated with a suitable coating layer which substantially prevents fat degradation during storage. Suitable coating materials are sugars, starch, hydrolysed starch, starch derivatives, polyols such as polyethylene glycol, cellulose acetate phthalate, polyvinyl acetate phthalate, hydroxypropyl methylcellulose phthalate, and cellulose or cellulose based compounds containing e.g. hydroxypropylcellulose, methyl cellulose, hydroxypropyl methyl cellulose and/or hydroxyethyl cellulose, and mixtures thereof. Optionally coating improving agents may be added. The lipase can, for instance, be produced as a granule or can be transferred onto a core material (e.g. using spraying technologies). Both methods result in enzyme particles having a granule shape. The production of such enzyme granules is known.

[0016] In general the core materials used would be of food grade quality. NaCl is an example of a core material which may be used.

[0017] In general the amounts of coating material will

be 1 to 25 w/w% of the final enzyme granule, preferably 3 to 15 w/w%.

[0018] The coated lipase can be added to compositions to improve the properties of bread. Normally bread is made from a dough comprising flour, water, yeast and in general salt. In many cases additional ingredients (such as enzymes) are added to improve the quality of the dough or bread. These ingredients can be added separately or added as a premix. Such a premix would be included in the term composition as used in this application.

[0019] The lipase may be a plant, animal or microbial lipase, and may be obtained from these sources. Preferably microbial lipase is used. As an example, lipase from *Rhizopus oryzae*, commercially available from Gist-brocades under the trademark Fermizyme L10000, may be used. Other suitable lipases can be obtained from *Humicola*, *Rhizomucor*, *Candida*, *Aspergillus*, *Rhizopus* or *Pseudomonas species*.

[0020] Lipase activity can be measured by pH-stat monitoring the production of free fatty acids from olive oil. 1 PLi unit is the amount of enzyme needed to produce 1 μ mole free fatty acid per minute at pH 7.5 and 37 $^{\circ}$ C from a neutral olive oil/water emulsion.

[0021] The following examples illustrate the invention:

Example 1

[0022] 367 kg liquid lipase ultrafiltrate (activity: 17500 PLi/g, dry matter: 135g/l) was sprayed in a fluidized bed granulator at 40 $^{\circ}$ C under pressure (4 bars) and with a flow rate of 1300g/min on 295 kg sieved sodium chloride (granule size: 60 μ m <95% <300 μ m). In the meantime a solution was prepared by mixing 41 kg maltodextrin (DE12, commercially available from ROQUETTE, Lestrem, France) and 2.14 kg Pharmacoat (Hydroxypropyl methylcellulose, commercially available from SEPPIC, Paris, France) in 64 kg demineralized water. This solution was sprayed (after the lipase had been applied to the NaCl carrier) at 40 $^{\circ}$ C under pressure (4 bars) with a flow rate of 1300g/min. Continuous air flow (6500m³/h) was maintained during both spraying operations.

[0023] Drying was then carried out by heating at 42 $^{\circ}$ C for 10 minutes while maintaining the same continuous air-flow (6500m³/h). The temperature was then finally brought down to 25 $^{\circ}$ C under continuous air-flow. This yielded 439 kg coated lipase:

activity:

12700 PLi/g (i.e. enzymatic yield is 87%)

moisture:

8.1%

granule size distribution:

125 μ m<41%<315 μ m

315 μ m<51%<400 μ m

thickness coating layer:

10 μ m.

Example 2

[0024] 301 Kg liquid lipase ultrafiltrate (activity: 17500 PLi/g, dry matter: 135g/l) was sprayed at 40 $^{\circ}$ C under pressure (5 bars) and with a flow rate of 1300g/min on 242 kg sieved sodium chloride (granule size: 60 μ m<95%<300 μ m). In the meantime a solution was prepared by mixing 33 kg maltodextrin and 1.75 kg Pharmacoat in 53 kg demineralized water. This solution was sprayed (after the lipase had been applied to the NaCl carrier) at 40 $^{\circ}$ C under pressure (5 bars) with a flow rate of 1000g/min. Continuous air flow (7000m³/h) was maintained during both spraying operations.

[0025] Drying was then carried out by heating at 42 $^{\circ}$ C for 12 minutes while maintaining the same continuous air-flow (7000m³/h). The temperature was then finally brought down to 25 $^{\circ}$ C under continuous air-flow (6500m³/h). This yielded 361 kg coated lipase:

activity:

13400 PLi/g (i.e. enzymatic yield is 92%)

moisture:

7.2%

granule size distribution:

125 μ m<59%<315 μ m

315 μ m<37%<400 μ m

thickness coating layer:

10 μ m.

Example 3

[0026] The following two compositions were prepared:

Salt	42 %	42 %
Hard fat soy 38	4.8 %	24 %
Fat kernels 80% soy fat 38	24 %	19 %
Soy flour	19 %	9.45 %
Starch	9.2 %	
Fermizyme L10000	1 %	
Coated lipase, 13400 Pli/g		0.75 %

These compositions are examples of compositions which may be used to improve the properties of bread.

[0027] Fermizyme L10000 is a powder lipase standardized to 10000 PLi/g. The coated lipase is from Example 2.

[0028] The compositions were stored at 25 $^{\circ}$ C. Every two to three days the smell of the compositions was judged. The composition containing Fermizyme L10000 started getting rancid after two days. However, in the composition containing coated lipase no rancidity developed within 60 days. The lipase activity was not signifi-